

MEDIPHOT

DATA-SHEET MEDIPHOT Automatic X-Ray Film Processors

Programmable microprocessor, controls the solution temperatures, dryer temperature, transport speed, processing time, replenishment, water saver and drive motor.

Programmable microprocessor, activates the automatic standby, anti-oxidation and anti-crystallization cycle, automatic start/stop function and replenishment pumps.

Intermediate rinse bath facilities, avoiding chemicals build-up and crystallization on squeeze rollers, helping to save daily cleaning time and replenishment costs.

Maintenance free inline precision gearing for the transport system and for the racks.

Processor is able to process roll film at any length as well. Feed and pick-up devices are available for all our processors.

Replenishment exactly according to the amount of film area fed into the processor – sensors for exact film area detection.

Processing chemicals are replenished also when the processor is in standby. The microprocessor controlled anti-oxidation replenishment cycle compensates air oxidation of chemistry during standby mode of processor.

Slim rack design – less air oxidation of chemicals, less chemistry volume in processor tanks – quick turnover by replenishment of whole tank content - stabile properties of processing chemicals.

Warm air dryer systems with safety switch facility.

Staggered rollers rack transportation system, no spring tensioned, opposed rollers or metal guides used.

Technical Specifications

cm (inch)

Type of Processor	MP 900E	MP 943	MP 902	MP 903
Max. Film Width	36 (14)	43 (17)	43 (17)	43 (17)
Min. Film Width	7,5 (3)			
Min. Film Length	10 (4)			
Tanks (PVC)	3			
Tank cap. (approx) lt.	2,6	6,5	7,5	10
Dev/Fix Temp. Range	18 – 43° C (64 – 109° F)			
Dryer Temp. Range	fixed	max. 60° C (140° F)		
Min. Cycle Time	90 sec	(60) 90 sec (dry to dry)		
Var. Cycle Time	3 programs	preprogrammable up to 10 (13) min extended proc. cycle		
Capacity at 90 sec Films/hour 35x43 cm (14x17")	69 cm / min (27"/min) 96	100 cm/min (40"/min) 171	125 cm/min (50"/min) 214	175 cm/min (70"/min) 300
Replenishment	acc. film area, variable/programmable 0 – 800 ml/m ²			
Electrical Power Supply all 50/60 Hz	1,7 kW 230 V~	3,1 kW 230 V~	3,4 kW 230 V~	5,4 kW 3~230 V or ~400/230
Water Supply/Drain	R ¾", 7 – 15 °C, 3 – 6 bar, approx. 1,5 – 2 l/min./32 mm (5/4 inch) hose or tube			

COLENTA LABORTECHNIK
 GmbH & Co. KG
 Neunkirchner Strasse 117
 2700 Wiener Neustadt
 AUSTRIA
 Tel.: +43-2622-28311-0
 Fax: +43-2622-28311-7
 E-mail: office@colenta.at
<http://www.colenta.at>

More info regarding COLENTA Medical Product Line see <http://www.colenta.at>